

## :: ProFlex Mercury

29 x 35 mm

### CHARACTERISTICS

The Carsystem ProFlex Mercury is optimally for the manual dry sanding process of dust inclusions and imperfections in the painted surface.

### APPLICATION

- To remove dust inclusions & imperfections in the paint surface
- Perfect for dry sanding
- Reduces the polishing time
- High removal
- Uniform sanding pattern
- No more wet sanding
- Work more clean & efficient

### PRODUCT DATA

Type: Self-adhesive sanding sheets

Size: 29 x 35 mm

Carrier material: Film

Bonding: Special treated corundum in modified resin paper: integrated

Abrasive grit type: Special treated corundum

Dispersion: Half open

Hole system: No holes

Grits: P 2000, P 2500, P 3000



03/2018

## HANDLING

The CS ProFlex Neptune can be processed by hand. We recommend the following additional product:

- Processing by hand with the CS ProFlex Mercury Sanding Block 154.297

## SAFETY ISSUES

The before mentioned technical data and information, especially the recommendations for applying and using our products, are based on our current knowledge and experience when applied under normal conditions. In practice, the materials, surfaces or site conditions are so different that no warranty regarding the working results or liability, arising out of any relationship, can be inferred neither from this information nor from a verbal consultation, except we are charged with intent or gross negligence. In this case the user is obliged to prove that he has informed us about all points required for a proper and promising judgement in writing, in time and completely. Patent rights of any third party are to be observed. Furthermore, our general sales and delivery Terms and Conditions and the latest Technical Data Sheet, which should be demanded, apply.

Directions for handling and waste disposal are in our Security Safety Data Sheet and the specifications of the Employers Liability Insurance Association for the chemical industry.

Copyright VOSSCHEMIE